

HERTRON STONE SYSTEMS

MARBLE SUPREME



POLISHING COMPOUND WITH HARDENING AGENTS

MARBLE SUPREME POLISHING COMPOUND

MARBLE SUPREME POLISHING COMPOUND is a ready mixed polishing paste for polishing marble, travertine, limestone and terrazzo, that has been diamond cut to 400 or 800 grit.

MARBLE SUPREME POLISHING COMPOUND can be used to restore worn marble, travertine, limestone and terrazzo, it also helps to provide initial water/stain resistance.

MARBLE SUPREME POLISHING COMPOUND is easy to use. Requires very simple instructions to produce beautifully polished stone with great depth.

MARBLE SUPREME POLISHING COMPOUND produces a deeper, clearer polish, 15 to 20 percent faster than competitive products tested. HERTRON has used it's 50 years of know how, to ensure a longer lasting shine requiring less maintenance.

DIRECTIONS FOR USE: Ensure that the area to be polished is free of all topical coatings and soiling. Protect all surrounding surfaces with Tape & Drape. Select an area of approximately 40 sq ft for the polishing process. Lightly wet the floor with clean water and place 1 scoop (¼ cup) of MARBLE SUPREME in the center of the area to be worked. Utilizing a red pad or natural hair, work the MARBLE SUPREME POLISHING COMPOUND over the area with a 175 to 300 RPM floor machine. The consistency of the slurry should be fluid enough to achieve even coverage. If the slurry becomes too dry, add water as needed. After making several side to side passes, squeegee back the slurry to determine that a consistent level of polish is achieved. Once the section is properly polished, wet vacuum the slurry, rinse with clear water and wet vacuum again. Complete large areas in checkerboard fashion, overlapping sections to blend. If the desired result is not obtained, a second application may give desired result. If after second application desired polish is not achieved the area may be too badly worn and require the use of other Hertron products to achieve desired polish.

Surface should be sealed with HERTO SEAL, after surface is thoroughly dry. This will help protect surface from water and stain damage.

NOTE: MARBLE SUPREME POLISHING COMPOUND will have a tendency to settle/separate in storage. Always stir the contents well prior to use, and from time to time during use. Replace the bucket lid as soon as possible and ensure that lid is firmly replaced when stored. If paste has dried out to much to prevent mixing prior to re-use, a small amount of water may be added to facilitate mixing.

COVERAGE: Approximately 250 sq ft per pound.

How to maintain your MARBLE SUPREME POLISH:

Floors should be dust mopped every day or more often as conditions dictate.

Mop with Hertron Stone Soap daily or as conditions dictate, making sure to change mop water regularly to insure dirty mop water is not being used.

CAUTION: Contains acid. Chemical product. Keep out of reach of children.

PERSONAL PROTECTIVE EQUIPMENT: Always wear appropriate personal protective clothing when using chemicals.

HERTRON STONE SYSTEMS

HERTRON INTERNATIONAL, LLC.

CHARLOTTE, NC 1-800-438-5066

MADE IN USA